

TI-FLOPPY-DRIVES ALL (TI and Non-TI)

VENDOR	PART / NUMBER	DESCRIPTION (SORT: krpm-Produkt-Bauform)	Housing / Interface	CAPACITY (form.) / NORM	Format / Socket	(k)rpm / MHz / Bus	RAM TYPE HDD Ports/Speed Tracks	TI-99 1=1inPEB 2=2inPEB 80=withMod E=external N=NO
BASF	???	xx TPI -	5.25" HH	??	DS/DD	300	??	2
Canon	MD211	48 TPI -	5.25" HH	180K / 200 K	DS/DD	300	40 Tracks	1
Canon	MD220	48 TPI - 3ms - (210,110,6ms)	5.25" HH	360 K / 400 K	DS/DD	300	80 Tracks	0
Canon	MD221	48 TPI -	5.25" HH	360 K / 400 K	DS/DD	300	80 Tracks	1
CDC	9409	48 TPI - 9 sec/track	5.25" FH	360 KB / 500K	DS/DD	300	40 Tracks	1
CDC	9428	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	1
Chinon	F-353	135 TPI - 10 sec/track - 512 Byte/Sec	3.5"	390 KB	SS/DD	300	80 Tracks	N
Chinon	FZ-502	48 TPI - 9 sec/track - Resistor via Jumper	5.25" HH	360 KB / 500 K	DS/DD	300	40 Tracks	1
Chinon	FZ-506 (FZ=Slim, F	96 TPI - 500 kbits	5.25" HH	1200 MB	DS/HD	360	160 Tracks	?
Chinon	C-354	135 TPI - 18sec/track - 250 kbits	3.5"	720 KB / 1 MB	DS/DD	300	160 Tracks	N
Chinon	FZ-354 (A1200)	135 TPI	3.5"	880 KB	DS/DD	300	80 Tracks	?
Chinon	FZ-357A (Amiga)	135 TPI	3.5"	880 KB	DS/HD	360	80 Tracks	?
for Amiga	??	67,5 TPI - DS0 DS1	3.5" EXT	880 KB	DS/DD	300	40 Tracks	E
Epson	SD521	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	2
Epson	SMD110	68.5 TPI - 16 sec/track 6ms 300mA-RW	3.5"	164 KB	SS/DD	300	40 Tracks	N
Epson	SMD120	68.5 TPI - 16 sec/track 6ms 300mA-RW	3.5"	328 KB	DS/DD	300	80 Tracks	E
Epson	SMD130	135 TPI - 16 sec/track 3ms 300mA-RW	3.5"	328 KB	SS/DD	300	80 Tracks	?
Epson	SMD140	135 TPI - 16 sec/track 3ms 300mA-RW	3.5"	656 KB	DS/DD	300	160 Tracks	?
Fujitsu	M2551A	48 TPI - 9 sec/track	5.25" HH	360 KB / 500 K	DS/DD	300	40 Tracks	?
Hitachi	HFD505B	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	2
Lotharek	HxC	** TPI - ALL given formats, depending on controller	3.5" 1in	90/180/360/720/1440	**/**	*	ALL	2
HP	FDD-USB	-	3.5" 1in	1.44 MB	USB/extern	?	-	-
HP	390164-B21	PL DL360G4p / DL580	3.5" 1in	1.44 MB	intern slim	360	-	-
HP	361402-001	zB DL360 G4 (intern Teac)	3.5" 1in	1.44 MB	intern slim	360	-	-
Magnetic Peripha	BR8B1A	48 TPI -	5.25" ??	180 / 360 KB	DS/SD	300	40 Tracks	1
Matsushita	JA551	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	1
Matsushita	JA551N	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	1
Micropolis	115V	96 TPI -	5.25" FH	720 KB	DS/QD	300	80 Tracks	80?
Mitsubishi	M4851	48 TPI-	5.25" HH	360 KB	DS/DD	300	40 Tracks	2
Mitsubishi	M4851-112M	48 TPI - 6 ms - 16Sec	5.25" HH	180 / 360 KB	DS/DD	300	40 Tracks	1
Mitsubishi	M4851-362U	48 TPI - 6 ms - 16Sec	5.25" HH	180 / 360 KB	DS/DD	300	40 Tracks	1
Mitsubishi	M4853	96 TPI - 18sec/track (&16/3interlace)	5.25" HH	720 KB / 1MB	DS/QD	300	80 Tracks	80
Mitsubishi	MT501A	40 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	2
Mitsumi	D353M3	135 TPI- 3ms - 9/15/18sec	3.5" 1in	720 / 1.2/ 1440 KB	DS/HD	300/360	160/154 Tracks	E
Mitsumi	D353M3D	135 TPI- 3ms - 9/15/18sec	3.5" 1in	720 / 1.2/ 1440 KB	DS/HD	300/360	160/154 Tracks	E
Mitsumi	D359M3D	135 TPI- 3ms - 9/18sec (Spare.for BackPack, NEU)	3.5" 1in	720 / 1440 KB	DS/HD	300	160 Tracks	E

TI-FLOPPY-DRIVES ALL (TI and Non-TI)

VENDOR	PART / NUMBER	DESCRIPTION (SORT: krpm-Produkt-Bauform)	Housing / Interface	CAPACITY (form.) / NORM	Format / Socket	(k)rpm / MHz / Bus	RAM TYPE HDD Ports/Speed Tracks	TI-99 1=1inPEB 2=2inPEB 80=withMod E=external N=NO
Mitsumi	D359T5	?	3.5" 1in	720 / 1440 KB	DS/HD	300	160 Tracks	E
MicroSolutions	014350 Series 5 Dr	135 TPI - BackPack ext (NT Bantan: 5V 1A 8W AP05M-US 110	3.5" EXT	720 / 1440 KB	DS/HD	300	160 Tracks	E
MPI MicroPeriph	51	48 TPI -	5.25" FH	360 / 720 KB	DS/DD	300	40 Tracks	1
MPI MicroPeriph	52SA	48 TPI - 9sec/track 250kbits	5.25" FH	360 KB / 500 K	DS/DD	300	80 Tracks	1
MPI MicroPeriph	B51	48 TPI -	5.25" FH	90 KB	SS/DD	300	40 Tracks	1
MPI MicroPeriph	B52	48 TPI -	5.25" FH	360K	DS/DD	300	40 Tracks	1
MPI MicroPeriph	B501C	48 TPI -	5.25" HH	360K	DS/DD	300	40 Tracks	1
MPI MicroPeriph	B502B	48 TPI -	5.25" 1/2L	360K	DS/DD	300	40 Tracks	1
Mitsumi/Newtroni	D357K	48 TPI - DS0-DS3	3.5" 1in	720 KB	DS/DD	300	80 Tracks	?
Mitsumi/Newtroni	D503V	48 TPI - (MITSUMI) Strombuchse & Teil abgebrochen (2015)	5.25" ??	360 KB	DS/DD	300	40 Tracks	1
Mitsumi/Newtroni	D509V	48 TPI -	5.25" HH	360KB / 1.2MB	DS/HD	300/360	80 Tracks	?
Mitsumi/Newtroni	D509V2	48 TPI -	5.25" HH	360KB / 1.2MB	DS/HD	300/360	80 Tracks	?
Mitsumi/Newtroni	D509V3	48 TPI -	5.25" HH	180 / 360 KB / 1.2MB	DS/DD/HD	300/360	80 Tracks	?
Mitsubishi	M4851	48 TPI - 6ms - 40 Zylinder?	5.25" HH	320K / 500K	DS/DD	300	40 Tracks	1
National	JA5512N	48 TPI - (MITSUMI)	5.25" HH	360K	DS/DD	300	40 Tracks	1
NEC	FD-1036A	135 TPI - 3ms - 16 Sec/Track-256bytes/sec - 250 kbits DS0-D	3.5" 1in	320 KB / 640 KB	DS/HD	300	160 Tracks	?
NEC	FD-1157C	96 TPI - 15 Sec/Track 500 kbits	5.25" HH	1.2 MB 1.6MB	DS/HD	300/360	160 Tracks	N
Panasonic	JA5512N	48 TPI -	5.25" HH	360K	DS/DD	300	40 Tracks	1
Panasonic/Matsu	JU-253-173P	135 TPI - 3ms -	3.5" 1in	1 MB	DS/HD	300	9sec/160 Tr.	E
Panasonic	JU-257-343P	135 TPI - 3ms -	3.5" 1in	1 / 2 MB	DS/HD	300	9sec/160 Tr.	E
Panasonic	JU-364-252	xx TPI - no resistorpack	3.5" 1in	360 KB	DS/DD	360	9sec/80 Tr.	?
Panasonic	JU-455-5AAG	48 TPI -	5.25" ??	360 KB	DS/DD	300	40 Tracks	1
Panasonic	JU-475-4 AKO	96 TPI - #06 - 3ms - 15Sec/Track	5.25" ??	360 / 1200 KB	DS/HD	360	80 Tracks	1
Pertec	FD200	48 TPI -	5.25" ??	360 KB	DS/DD	300	40 Tracks	1
QumeTrak	142	48 TPI - #07-#08 12ms(6 opt) 16sec/T	5.25" HH	360 KB / 500	DS/DD	300	40 Tracks	1
QumeTrak	142LX	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	1
QumeTrak	542	48 TPI -	5.25" FH	360 KB	DS/DD	300	40 Tracks	1
Remex	RFD480	48 TPI -	2/3	360 KB	DS/DD	300	40 Tracks	1
Sanyo	FDA5200	48 TPI - for IBM-PC	5.25" HH	360 KB	DS/DD	300	40 Tracks	N
Sanyo	SM5480	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	2
Samsung	SFD-321B	135 TPI	3.5"	1/2MB	DS/HD	300/360	80 Tracks	?
Shugart	SA-40L	48 TPI -	5.25" FH	90 KB	DS/DD	300	40 Tracks	1
Shugart	SA-400L	48 TPI - ORIG TI-Drive	5.25" FH	90 KB	SS/DD	300	40 Tracks	1
Shugart	SA455	48 TPI - black z Zt DSK1 - 1 PIN für Jumper DS3 ab! (2015 bc	5.25" HH	360 KB (0.5MB)	DS/DD	300	40 Tracks	2
Shugart	SA455-2	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	2
Shugart	SA455-3AA	48 TPI - black z Zt DSK3 - DoubleHead (IBM)	5.25" HH	360/720 KB	DS/DD	300	40 Tracks	?

TI-FLOPPY-DRIVES ALL (TI and Non-TI)

VENDOR	PART / NUMBER	DESCRIPTION (SORT: krpm-Produkt-Bauform)	Housing / Interface	CAPACITY (form.) / NORM	Format / Socket	(k)rpm / MHz / Bus	RAM TYPE HDD Ports/Speed Tracks	TI-99 1=1inPEB 2=2inPEB 80=withMod E=external N=NO
Shugart	SA465	96 TPI -	5.25" HH	720 KB (1.0MB)	DS/QD	300	80 Tracks	80?
Shugart	SA475	96 TPI -	5.25" HH	1.6MB	DS/QD	300	80 Tracks	N
Siemens	FDD100-5	48 TPI - ORIG TI-Drive GER (as 90K SS)	5.25" FH	90 KB	SS/DD	300	40 Tracks	1
Siemens	FDD200-5	48 TPI	5.25" FH	360 KB	DS/DD	300	40 Tracks	1
Sony	MP-F110-05	96 TPI - AMIGA extern	3.5" 1in	720KB/1.44MB	DS/DD	300	80 Tracks	?
Sony	MP-F17W-17 / MFI	96 TPI -	3.5" 1in	1.44 MB	DS/HD	360	80 Tracks	?
Sony	MP-F920	96 TPI -	3.5" 1in	720KB/1.44MB	DS/HD	300	80 Tracks	80
Tandon	TM50-1	48 TPI - 15ms HS, 800mA	5.25" HH	180 KB (90KB@TI)	SS/DD	300	40 Tracks	1
Tandon	TM55-1	48 TPI -	5.25" HH	90 KB	SS/DD	300	40 Tracks	1
Tandon	TM55-2	48 TPI - 15ms HS, 800mA	5.25" HH	360 KB (500)	DS/DD	300	80 Tracks	1
Tandon	TM55-4	96 TPI -	5.25" HH	720 KB	DS/QD	300	80 Tracks	80?
Tandon	TM65-2	48 TPI -	5.25" HH	360 KB	DS/DD	300	40 Tracks	?
Tandon	TM65-2L	96 TPI -	5.25" HH	1600 KB	DS/QD	300	80 Tracks	N
Tandon	TM100-1	48 TPI -	5.25" FH	180 KB	SS/DD	300	40 Tracks	1
Tandon	TM100-2	48 TPI -	5.25" FH	380 KB	DS/DD	300	40 Tracks	1
Tandon	TM100-2A	48 TPI -	5.25" FH	360 KB	DS/DD	300	40 Tracks	1
Tandon	TM100-4	96 TPI -	5.25" FH	720 KB	DS/QD	300	80 Tracks	80
Tandon	TM100-4-1	100 TPI -	5.25" FH	720 KB	DS/QD	300	100 Tracks	N
TEAC	FD-35-F-03U	135 TPI - 3ms - 40/80T OK, DSDD&DSHD, 1.4Watt	3.5"	2 / 1 MB	DS/DD	300	80 Tracks	N
TEAC	FD-235-HF	135 TPI - 3ms - 40/80T OK, DSDD&DSHD, 1.4Watt 0.3A, 500k	3.5"	1.44 / 2MB	DS/HD	300	160 Tracks	2
TEAC	FD-50A	48 TPI -	5.25" FH	180 KB / 250 K	SS/SD	300	40 Tracks	N?
TEAC	FD-55A-*	48 TPI - #00 - 6ms - 16 Sec/Track - 250 kbits	5.25" HH	180 KB / 250 K	SS/DD	300	40 Tracks	2
TEAC	FD-55B-01-U	48 TPI - #00 - 6ms - 16 Sec/Track	5.25" HH	180 / 360 KB	DS/DD	300	80 Tracks	2
TEAC	FD-55BR 115-U5	48 TPI - #04 - 6ms - 16Sec/Track Teil noch befest	5.25" HH	180 / 360 KB	DS/DD	300	80 Tracks	2
TEAC	FD-55BV	48 TPI - 6ms - 16 Sec/Track (for IBM)	5.25" HH	180 / 360 KB	DS/DD	300	80 Tracks	2
TEAC	FD-55E-*	96 TPI - #00 - 3ms - 16 Sec/Track	5.25" HH	180 / 360 KB	SS/QD	300	80 Tracks	80?
TEAC	FD-55F 03-U	96 TPI - #05 - 3ms - (EX-"160"-Track :) (2015) - ?16 Sec/Track	5.25" HH	1200 KB (800-1600 unft	DS/QD	300	160 Tracks	80?
TEAC	FD-55GFR 149-U5	96 TPI - #02 #09 - 3ms - beige, #2 wohl defekt - 15 Sec/Track	5.25" HH	1200 KB (800-1600 unft	DS/QD	360	154 Tracks	N
TEAC	FD-55GFR 193-U	96 TPI - #03 - 3ms - in Tüte 51-93 193-U - 15 Sec/Track	5.25" HH	1200 KB (800-1600 unft	DS/QD	360	154 Tracks	N
TEAC	FD-55GFR 7193-U	96 TPI - #01 - 3ms - PCXPVintage - 15 Sec/Track	5.25" HH	1200 KB (800-1600 unft	DS/QD	360	154 Tracks	N
TEAC	FD-55GFV-17-U	96 TPI - xms - 15 Sec/Track	5.25" HH	1200 KB 360 KB	DS/DD	300/360	160 Tracks	N
TEC	FB-501	48 TPI - 9 sec/track	5.25" HH	180 KB	SS/DD	300	80 Tracks	2
TEC	FB-503	48 TPI -	5.25" HH	90 KB	SS/DD	300	40 Tracks	2
TI	PHP1250	48 TPI -	5.25" FH	90 KB	SS/SD	300	40 Tracks	1
TI	PHP1850	48 TPI -	5.25" FH	90 KB	SS/SD	300	40 Tracks	1
Toshiba	5401	48 TPI -	5.25" FH	90 KB	SS/DD	300	40 Tracks	1

